


### SPECIFICATION

- Rating:** 1A 125V AC / 30mA 5V DC.
- Contact resistance:**  $\leq 50m\Omega$  .(initial)
- Operating force:** 30±15g.
- Mechanical life:** 500,000 Cycles.
- Electrical life:** 10,000 / 500,000 Cycles.
- Insulation resistance:**  $\geq 100M\Omega$  500V DC.(initial)
- Withstand voltage:** 500V AC 1 minute.(initial)
- Operating temperature range:** -25°C ~ +65°C.
- Soldering temperature:** 250°C Max for 3 Sec.
- Ambient humidity range:** <85% RH.

### SCHEMATIC



RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±  
.X ± 0.20  
.XX ± 0.10  
.XXX ±  
ANG ±

照片框

### ORDER INFORMATION

MISW-R51L14-xxx-LF

SERIES

LEADFREE

025:25g

030:30g

035:35g

040:40g

PUSH LEVER 14mm

DIP 90°  
PITCH:5.08mm

DESCRIPTION: Micro Switch