


保存注意事項：

Precautions for preservation:

1. 此產品為鍍銀或鍍金產品，裸露在空氣中極易氧化，會造成冷焊或焊接不良。建議拆封後，未使用完的開關務必放入袋內，並置入乾燥劑後密封袋口，以防氧化。  
This is a silver-plated or gold-plated product, which can be easily oxidized when exposed to air that may cause cold welding or poor welding. We recommend that after unpacking, the unused switch must be preserved into a sealed bag with desiccant to prevent oxidation.
2. 若產品拆封後，客戶未盡妥善保存之責，造成產品氧化，我司無法負保固責任。  
After the product is unpacked, if the customer fails to properly preserve the product, causing the product to oxidize, our company cannot be held responsible for the warranty.

SCHEMATIC



**SPECIFICATION**

Rating: 3A 125V AC / 1.5A 250V AC.  
 Contact resistance:  $\leq 100m\Omega$  (initial)  
 Insulation resistance:  $\geq 100M\Omega$  at 500V DC.  
 Withstand voltage: 500V AC for 1 minute.  
 Operating temperature:  $-25^{\circ}C \sim +65^{\circ}C$ .  
 Ambient humidity used:  $< 70\%RH$ .  
 Operating force: 20~50g.  
 Mechanical life: 500,000 Cycles.  
 Electrical life: 10,000 Cycles.  
 Note1: Unwashable, don't be immerged by epoxy and organic solvent.  
 Note2: Please do not scale the drawing comparing to real product and kindly measure the size of real product.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

X,  $\pm$   
 .X  $\pm$  0.30  
 .XX  $\pm$  0.20  
 .XXX  $\pm$   
 ANG  $\pm$

照片框

ORDER INFORMATION

MISW-RV51L11-xxx-LF

SERIES

LEADFREE

020.030.040.050g

LEVEL 11.8mm

CONTACT PITCH 5.08mm

REVERSED

DIP 90°

DESCRIPTION: Tiny Micro Switch