



OF max.	160 g
RF min.	42 g
PT max.	2.7 mm
OT min	2.4 mm
MD max.	0.5 mm
FP max.	32.5 mm
OP	30.2 ±0.4mm

Specifications

Rating

20(4)A 250VAC EN 61058-1
 15A 125VAC or 250VAC UL 1054
 1/2A 125VDC 1/4A 250VDC
 1/8HP 125VAC 1/4HP 250VAC

Contact Resistance

15mΩ max. (initial)

Insulation Resistance

100MΩ min. (at 500V DC)

Dielectric Strength

Between terminals of same polarity
 AC 1000V (50/60Hz for 1minute)

Electrically Life

100,000 operations min

Mechanically Life

1,000,000 operations min.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.20

.XX ± 0.10

.XXX ± 0.05

ANG ±

PJECTION

照片框

ORDER INFORMATION

MISW-SM4L26R-160-LF

SERIES

LEADFREE

160g

ROLLING TYPE

LEVEL 26.2mm

SCREW M4

DESCRIPTION: