



PCB LAYOUT/TOP VIEW

**SPECIFICATIONS**

**MATERIAL:**

1. Housing : PBT Polyester UL94V0
2. Color : Gray
3. Contacts : 0.45mm Diameter Phos-Bronze Plated With Hard Gold

**ELECTRICAL:**

1. Current Rating : 1.5 AMP MAX
2. Voltage Rating : 150 VAC MAX
3. Contact Resistance : 30 milliohms MAX, initial
4. Insulation Resistance : 500 Megohms MIN
5. Dielectric Withstanding Voltage : 1000 VAC, 1min

MJ14S-GE<sub>xx</sub>-1010-LF

LEADFREE

- 03:3u" GOLD
- 06:6u" GOLD
- 15:15u" GOLD
- 30:30u" GOLD
- 50:50u" GOLD

RoHS Compliant



PART NO. MJ14S-GE<sub>xx</sub>-1010

DWG NO. MJ14S-GE<sub>xx</sub>-1010

FILE NO.

CHECKED BY CY

DRAWING BY

TOLERANCES ARE

- .X ± 0.2
- .XX ±
- .XXX ±
- AWG

DESCRIPTION:

10P Mini Low Profile Modular Jack

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION



AREA

REVISIONS

HK

DATE