



PCB LAYOUT / TOP VIEW

**MATERIAL & FINISH**

Housing : PBT. UL94V-0, grey or black  
 Insert: PBT. UL94V-0, 6P&4P-black, 8P&10P-gray  
 Conductor:

- Round pin: 0.45 mm diameter phosphor bronze,  
 Plating: Gold plated over nickel.
- or
- Stamping pin 0.35 × 0.42 mm phosphor bronze,  
 Plating: Gold plated over nickel on contact area,  
 Tin plated over nickel on solder area.

Temperature: -40°C to 70°C  
 Durability: 750 cycles min.

**ELECTRICAL**

Voltage Rating : 125 V  
 Current Rating : 1.5 A  
 Contact Resistance : 30 milliohms max.  
 Insulation Resistance : 500 megaohms min.  
 Dielectric Withstanding Voltage : 1000 V

position	contact	A	B	C
4P	4C	10.00	7.85	10.00
(6P)4P	4C	12.20	7.85	12.00
6P	2C/4C/6C	12.20	9.90	12.00
8P	8C	15.00	11.85	15.00
10P	10C	15.00	11.85	15.00

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1 : 1  
 DATE  
 SIZE A4 PPROJECTION

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

照片框

ORDER INFORMATION

MJ14S-xXxx-xxxx-LF

SERIES LEADFREE

K:BLACK 06:06u"GOLD 0404:4P4C  
 G:GRAY 15:15u"GOLD 0602:6P2C  
 NON EAR 30:30u"GOLD 0808:8P8C  
 50:50u"GOLD 1010:10P10C

DESCRIPTION: