



PCB LAYOUT / TOP VIEW

MATERIAL & FINISH

Housing & Insert: PBT, UL94V-0
 Conductor: 0.35 × 0.42 mm thickness phosphor bronze,
 Plating: Gold plated over nickel on contact area,
 Tin plated over nickel on solder area.
 Temperature: -40°C to 70°C
 Durability: 750 cycles min.

ELECTRICAL

Voltage Rating: 125 V
 Current Rating: 1.5 A
 Contact Resistance: 30 milliohms max.
 Insulation Resistance: 500 megaohms min.
 Dielectric Withstanding Voltage: 1000 V

position	contact	A	B	C	D	E
4P	4C	13.55	11.15	7.70	7.62	3.50
6P	2C/4C/6C	15.60	13.15	9.90	10.16	3.50
8P	4C/6C/8C	17.60	15.20	11.95	11.43	4.00
10P	10C	17.60	15.20	11.95	11.43	4.00

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30
 .X ± 0.30
 .XX ± 0.20
 .XXX ± 0.10
 ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

MJ15-KE06-xyyy-LF

SERIES LEADFREE

BLACK EAR 0404:4P4C
 06yy:6P2C.6P4C.6P6C
 08yy:8P4C.8P6C.8P8C
 1010:10P10C
 06u"GOLD

DESCRIPTION: