

注:

1. Insert: PA6T+30%G. F BLACK UL94V-0 (RoHS).
 2. Shielding: Copper Alloy with Nickel Plated (RoHS).
 3. Contact: 0.35X0.44mm Phosphor Bronze gold Plating Over Nickel (RoHS).
 4. Welding post: Copper Alloy with Nickel Plated (RoHS).
- ※MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
 ※凡标注▲记号为重点尺寸。

RECOMMENDED P.C.B LAYOUT TOP VIEW
 (COMPONENT SIDE TOLERANCE ±0.05)

Detail A Scale 4

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY


CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

X, ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 ANG ±



ORDER INFORMATION

MJ24B6-KXxxB5-0808-LF

SERIES	LEADFREE
8P8C	REAR TAB 5.85mm
06:06u" GOLD	
BLACK	
NON EAR	30:30u" GOLD

DESCRIPTION: