



PC BOARD COMPONENT SIDE SHOWN

DIM \ PORT	2X1	2X2	2X3	2X4	2X5	2X6	2X8
"A" ±0.25	13.20	25.15	45.21	49.00	60.95	72.89	96.77
"B"		11.94	23.88	35.81	47.75	59.69	83.57
"C" ±0.25	10.16	22.10	39.37	45.97	57.91	69.85	93.73

NOTES:

ELECTRICAL:

- VOLTAGE RATING : 125 VAC RMS.
- CURRENT RATING : 1.5 AMP.
- CONTACT RESISTANCE: 50 MILLIOHMS MAX.
- INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
- DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

- HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
- CONTACT MATERIAL : PHOSPHOR BRONZE ϕ 0.46mm.
- PLATING : GOLD PLATING OVER NICKEL.
- OPERATING LIFE : 750 CYCLES MIN.
- PCB RETENTION PRE-SOLDER : 1 LB MIN.
- PCB RETENTION POST-SOLDER : 10 LBS MIN.

ENVIRONMENTAL:

- STORAGE: -40°C TO +85°C.
- OPERATION: -40°C TO +85°C.

MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X \pm 0.25
.XX \pm 0.15
.XXX \pm 0.05
ANG \pm

P PROJECTION

照片框

ORDER INFORMATION

MJ25Bx-KX01-0808-LF

SERIES | | | | | LEADFREE
| | | | | 8P8C
| | | | | 01u" GOLD
| | | | | NON EAR
| | | | | BLACK
| | | | | 1~8 PORTS

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: