



| Contact Position | WIRE COLOR | LEADWIRE LENGTH | TIN Terminal |
|------------------|------------|-----------------|--------------|
| 1 | BLUE | 50mm | 3T |
| 2 | YELLOW | 50mm | 3T |
| 3 | GREEN | 50mm | 3T |
| 4 | RED | 50mm | 3T |
| 5 | BLACK | 50mm | 3T |
| 6 | WHITE | 50mm | 3T |

MATERIAL:

- 1.HOUSING:
2.WIRE:

- A. ABS UL 94V2.
A. UL1061 26 AWG.
B. STRANDED 7/0.16

- 3.CONDUCTOR:

- A. NICKEL THICKNESS 100-135U"
B. COLD THICKNESS 2.5-3.2U"

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ±

UNIT / mm

SCALE 1 : 1

.XX ±

DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

MJ623K-060626-050-LF

SERIES

6P6C

LEADFREE

50mm

26 AWG

6P6C

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: MODULAR JACK(623K) 6P6C L:50mm