



Electrical:

- 1.Voltage Rating:125 Vac Rms.
- 2.Current Rating:1.5 Amp.
- 3.Contact Resistance:40 Milliohms Max.
- 4.Insulation Resistance:1000 Me ohms Min @500 Vde.
- 5.Dielectric Strength:1000 Vac Rms 60Hz, IMin.

Mechanical:

- 1.Operating:750 Cycles Min.

Environmental:

- 1.Storage: - 40°C To +85°C.
- 2.Operation:-20°C To +75°C.

Mates With Modular Plug Conforming To FCC Part 68, Subpart F.

MATERIALS:

PLASTIC HOUSING:ENGINEERING THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0.

CONTACTS: PHOSPHOR BRONZE
PLATING: GOLD PLATING OVER NICKEL IN CONTACT.
TIN PLATING OVER NICKEL IN SOLDER AREA.

SHIELDED:BRASS WITH NICKEL PLATED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ± 0.50

CHECKED BY GENIUS

.X ± 0.38

UNIT / mm

SCALE 1 : 1

.XXX ± 0.10

DATE

ANG ± 3°

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

MJDF16C5-KX06B2-0808-LF

SERIES

LEADFREE

8P8C

BLACK

06u" GOLD

NON EAR

REAR TAB 2.75mm

DESCRIPTION: TOPENTRY PCB JACK(8P8C) Tiny Shielded Cat 5

煜倫股份有限公司

www.morethanall.com