



PCB LAYOUT / TOP VIEW

position	conductor	A	B	C	D
4P	4C	13.70	11.20	7.90	7.62
6P	2C/4C/6C	15.70	13.20	10.00	10.16
(8P)6P	2C/4C/6C	17.70	15.20	10.00	11.43
8P	8C	17.70	15.20	11.80	11.43
10P	10C	17.70	15.20	11.80	11.43

UNIT: m / m
TOL.: +/- 0.15

ELECTRICAL

Voltage Rating : 125 V
 Current Rating : 1.5 A
 Contact Resistance : 30 milliohms max.
 Insulation Resistance : 500 megaohms min.
 Dielectric Withstanding Voltage : 1000 V

MATERIAL & FINISH

Housing & Insert: PBT. UL94V-0, black
 Conductor: 0.35 × 0.42 mm thickness phosphor bronze,
 Plating: Gold plated over nickel on contact area,
 Tin plated over nickel on solder area.
 Temperature: -40°C to 70°C
 Durability: 750 cycles min.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MJDS12-KE06-xxxx-LF

SERIES | LEADFREE
 0404:4P4C
 1010:10P10C
 06u"GOLD
 EAR
 BLACK

DESCRIPTION: