



- NOTES:
- ELECTRICAL:
1. VOLTAGE RATING:125VAC RMS.
 2. CURRENT RATING:1.5AMP.
 3. CONTACT RESISTANCE:42MILLIOHMS MAX.
 4. INSULATION RESISTANCE:1000 MEGOHMS MIN @ 500 VDC.
 5. DIELECTRIC STRENGTH:1000 VDC RMS 60HZ. 1MIN.
- MECHANICAL:
1. HOUSING MATERIAL:NYLON 66, UL94V-0.
 2. CONTACT MATERIAL:PHOSPHOR BRONZE ϕ 0.46mm.
 3. PLATING:GOLD PLATING OVER NICKEL.
 4. OPERATING LIFE:750 CYCLES MIN.
 5. PCB RETENTION PRE-SOLDER:1 LB MIN.
 6. PCB RETENTION POST-SOLDER:10 LBS MIN.
- ENVIRONMENTAL:
1. STORAGE:-40 °C TO 85 °C.
 2. OPERATION:0 °C TO 70 °C.

RECOMMENDED PCB LAYOUT

MJF13Ax - KX03Ax - 0808

MULTIPOINT
A4 : 1X04
A5 : 1X05
A6 : 1X06
A8 : 1X08

GROUNDING PIN
A36: 3.57mm
A4: 4.57mm



PART NO. MJF13Ax-KX03Ax-0808

RoHS Compliant

DWG NO. MJF13Ax-KX03Ax-0808

CHECKED BY CY

TOLERANCES ARE

DESCRIP TION: TELEPHONE JACK 單層多PORT

FILE NO.

DRAWING BY

.X ± 0.2
 .XX ± 0.1
 .XXX ±
 AWG

AREA	REVISIONS	HK	DATE
------	-----------	----	------

煜倫股份有限公司

UNIT / mm

SCALE 1:1

PROJECTION