


PCB LAYOUT
(Top View)



CATEGORY 5
PCB LAYOUT

LED Designation :					
Code	Forward	Reverse	Code	Forward	Reverse
G	Green	—	5	Green	Yellow
Y	Yellow	—	6	Yellow	Green
3	Green	Red	9	Red	Green
4	Yellow	Red	0	Red	Yellow

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing (Option) :
 - PBT Glass Filled (UL 94V-0), Soldering Temperature:235°C
 - Nylon (UL 94V-0), Soldering Temperature:260°C
- Color : Black Color
- Spring Wire :
 - 0.35mm Thickness Phosphor bronze Gold Plating Over Nickel
- Shielded : Brass Plating Nickel
- Temperature Range : - 40°C / +85°C
- Durability : 500 Mating cycles Min.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MJF13C5LA4-KF06B4xx-0808-LF

SERIES

LEADFREE

8P8C

GY:GREEN / YELLOW

YG:YELLOW / GREEN

REAR TAB 4.06mm

BLACK FULL SPRING

06u" GOLD

DESCRIPTION: RJ45 Side Entry Shielded Jack With LED