


**PCB LAYOUT**  
(Top View)



The soldering temperature around 250-260 degree C for 3-5 second withstand.  
 Note : Total Cd(cadmium) Content< 5PPM(mg/kg)  
 Test Method : EN1122:2001 Method (ICP-AES)  
 : Total Pb(Lead) Content< 100PPM(mg/kg)  
 Test Method : US EPA3050B (ICP-AES)

LED Designation :					
Code	Forward	Reverse	Code	Forward	Reverse
G	Green	—	5	Green	Yellow
Y	Yellow	—	6	Yellow	Green
3	Green	Red	9	Red	Green
4	Yellow	Red	0	Red	Yellow

## SPECIFICATION :

### 1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.  
 Contact Resistance : 20milli-Ohm Max.  
 Rating Current : 1.5A Max.  
 Rating Voltage : 120V AC.  
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

### 2. Physical char.

Housing : Nylon (UL 94V-0)  
 Color : Black Color  
 Spring Wire : 0.35mm Thickness Phosphor Bronze  
 Gold Plating Over Nickel  
 Temperature Range : - 25 /+90 Deg C  
 Durability : 500 Mating cycles Min.

### 3. LED filings.

Forward DC Current : 20 mA  
 Forward Voltage : 2.2 Volts Typical

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 X, ±  
 .XX ±  
 .XXX ±  
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MJF13C5UL-KF50B34GG-0808-LF

SERIES

LEADFREE

8P8C

GREEN / GREEN

REAR TAB 3.43mm

50u" GOLD  
FULL SPRING

BLACK

DESCRIPTION: