


PCB LAYOUT
(Top View)



The soldering temperature around 250-260 degree C for 3-5 second withstand.
 Note : Total Cd(Cadmium) Content< 5PPM(mg/kg)
 Test Method : EN1122:2001 Method (ICP-AES)
 : Total Pb(Lead) Content< 100PPM(mg/kg)
 Test Method : US EPA3050B (ICP-AES)

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing : Nylon (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

3. LED filings.

- Forward DC Current : 20 mA
- Forward Voltage : 2.2 Volts Typical

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY		X. ±
CHECKED BY GENIUS		.X ±
UNIT / mm	SCALE 1 : 1	.XXX ±
DATE		ANG ±
SIZE A4	PROJECTION	

照片框

ORDER INFORMATION



DESCRIPTION: