



CATEGORY 5 PCB LAYOUT
(Top View)

Note : Total Cd(cadmium) Content< 5PPM(mg/kg)
 Test Method : EN1122:2001 Method (ICP-AES)
 Total Pb(Lead) Content< 100PPM(mg/kg)
 Test Method : US EPA3050B (ICP-AES)

LED Designation :

Code	Forward	Reverse	Code	Forward	Reverse
G	Green	—	5	Green	Yellow
Y	Yellow	—	6	Yellow	Green
3	Green	Red	9	Red	Green
4	Yellow	Red	0	Red	Yellow

SPECIFICATION :

1. Electrical Char.

Insulation Resistance : 500M-Ohm Min.
 Contact Resistance : 20milli-Ohm Max.
 Rating Current : 1.5A Max.
 Rating Voltage : 120V AC.
 Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

Housing : Nylon (UL 94V-0)
 Color : Black Color
 Spring Wire : 0.35mm Thickness Phosphor Bronze
 Gold Plating Over Nickel
 Temperature Range : - 25 /+90 Deg C
 Durability : 500 Mating cycles Min.

3. LED filings.

Forward DC Current : 20 mA
 Forward Voltage : 2.2 Volts Typical

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT / mm SCALE 1 : 1
 DATE

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

MJF13C5UL-KT50B34GG-0808-LF
 SERIES | | | | LEADFREE
 | | | | 8P8C
 | | | | GREEN / GREEN
 BLACK | | REAR TAB 3.43mm
 | | 50u" GOLD
 TOP SPRING

煜倫股份有限公司

www.morethanall.com

SIZE A4 PPROJECTION

DESCRIPTION: