



**Electrical:**

- 1.Voltage Rating:125 Vac Rms.
- 2.Current Rating:1.5 Amp.
- 3.Contact Resistance:20 Milliohms Max.
- 4. Insulation Resistance: 500M $\Omega$  Min
- 5.Dielectric Strength:AC 1500 V RMS 50Hz OR 60Hz 1 Min

**Mechanical:**

- 1.Operating:750 Cycles Min.

**Environmental:**

- 1.Storage:-40°C To +85°C.
- 2.Operation:-40°C To +70°C.

Mates With Modular Plug Conforming To FCC Part 68, Subpart F.

**MATERIALS:**

- PLASTIC HOUSING: ENGINEERING THERMOPLASTIC  
FLAMMABILITY RATING UL 94V-0.
- CONTACTS: PHOSPHOR BRONZE
- PLATING: GOLD PLATING OVER NICKEL IN CONTACT.  
TIN PLATING OVER NICKEL IN SOLDER AREA.
- SHIELD: COPPER ALLOY WITH TIN PLATED.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X.  $\pm 0.50$

CHECKED BY GENIUS

.X  $\pm 0.38$

UNIT / mm

SCALE 1 : 1

.XX  $\pm 0.25$

DATE

.XXX  $\pm 0.10$

ANG  $\pm 3^\circ$

照片框

ORDER INFORMATION

MJF13T056LA2-KF06B3YG-0808-LF

SERIES

LEADFREE

8P8C

YELLOW, GREEN

REAR TAB 3.05mm

06u" GOLD

FULL SPRING

BLACK

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

DESCRIPTION: