



Insertion Loss: 1-100MHZ -1.0dB MAX
 Return Loss: 1-30MHZ -16.0dB MIN
 30-60MHZ -14.0dB MIN
 60-80MHZ -10.0dB MIN
 Cross Talk: 1-30MHZ -40.0dB MIN
 30-60MHZ -35.0dB MIN
 60-80MHZ -30.0dB MIN
 CMR: 1M-100MHZ -35dB MIN
 Hi-Pot:1500v AC 6S 1mA
 Turn Ratio: 1CT:1CT+/-3%
 OCL:350uH MIN @ 100KHZ 100mV 8mA DC

Electrical:
 1.Voltage Rating:125 Vac Rms.
 2.Current Rating:1.5 Amp.
 3.Contact Resistance:40 Milliohms Max.
 4.Insulation Resistance:1000 Megohms Min @500 Vdc.
 5.Dielectric Strength:1000 Vac Rms 60Hz, 1Min.

Mechanical:
 1.Operating:750 Cycles Min.
Environmental:
 1.Storage:-40°C To +85°C.
 2.Opertion:-20°C To +75°C.

HOUSING: PBT BLACK UL94V-0

RoHS Compliant TOLERANCES ARE

DRAWING BY CY X. ± 0.50
 CHECKED BY GENIUS .X ± 0.38
 UNIT / mm SCALE 1 : 1 .XX ± 0.25
 .XXX ± 0.10
 ANG ± 3°

照片框

ORDER INFORMATION

MJF13T45LA2-KX06B3GY-0808
 SERIES 8P8C
 GREEN / YELLOW
 REAR TAB 3.05mm
 BLACK 06u" GOLD
 NON EAR

DESCRIPTION:

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司
 www.morethanall.com

DATE SIZE A4 PPROJECTION