

**MATERIALS:**

- HOUSING-DSM STANYL TE250F6 (NYLON-46)  
HEAT DEFLECTION TEMP.290°  
BLACK COLOR,UL94V-0
- CONTACTS-0.35mm THICK PHOS-BRONZE PLATED WITH HARD GOLD AND TIN/LEAD IN SOLDER AREA.
- SHIELD-0.25mm THICK COPPER ALLOY, PLATED WITH TIN-LEAD.

**ELECTRICAL:**

INSULATION RESISTANCE: 500 MEGOHMS MINIMUM  
CURRENT RATING: 1.5 AMPS  
VOLTAGE RATING: 150 VOLTS AC

**LED FALINGS:**

FORWARD DC CURRENT: 2mA  
FORWARD VOLTAGE: 1.8 VOLTS TYPICAL  
REVERSE VOLTAGE: 5 VOLTS MINIMUM  
POWER DISSIPATION: GRN.=24mW;YELL.=36mW

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS PART 68,SUBPART F.

PCB LAYOUT

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.25

UNIT / mm

SCALE 1 : 1

.XX ± 0.13


DATE

.XXX ±

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

MJF13UL-KF06B3GG-0808

SERIES 8P8C

BLACK LED1 / LED2

FULL SPRING REAR TAB 3.43mm

06u" GOLD

DESCRIPTION: 8POSITION LED SHIELDED FLAT PIN, SIDE ENTRY JACK

煜倫股份有限公司

www.morethanall.com