

**MATERIALS:**  
 · HOUSING-DSM STANYL TE250F6 (NYLON-46)  
 HEAT DEFLECTION TEMP.290°  
 BLACK COLOR,UL94V-0  
 · CONTACTS-0.35mm THICK PHOS-BRONZE PLATED  
 WITH HARD GOLD AND TIN/LEAD IN  
 SOLDER AREA.  
 · SHIELD-0.25mm THICK COPPER ALLOY,  
 PLATED WITH TIN-LEAD.

**ELECTRICAL:**  
 INSULATION RESISTANCE: 500 MEGOHMS MINIMUM  
 CURRENT RATING: 1.5 AMPS  
 VOLTAGE RATING: 150 VOLTS AC  
 LED FAILINGS:  
 FORWARD DC CURRENT: 2mA  
 FORWARD VOLTAGE: 1.8 VOLTS TYPICAL  
 REVERSE VOLTAGE: 5 VOLTS MINIMUM  
 POWER DISSIPATION: GRN.=24mW;YELL.=36mW

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS  
 PART 68,SUBPART F.

PCB LAYOUT

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES


煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY  
 CHECKED BY GENIUS  
 UNIT / mm SCALE 1:1  
 DATE  
 SIZE A4 PPOJECTION

TOLERANCES ARE  
 X, ±  
 .X ± 0.25  
 .XX ± 0.13  
 .XXX ±  
 ANG ±



ORDER INFORMATION

MJF13UL-KF06B3RG-0808  
 SERIES 8P8C  
 BLACK LED1 / LED2  
 FULL SPRING REAR TAB 3.43mm  
 06u" GOLD

DESCRIPTION: 8POSITION LED SHIELDED FLAT PIN, SIDE ENTRY JACK