



SPECIFICATION NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5 AMP
3. CONTACT RESISTANCE: 30mΩ MAX.
4. INSULATION RESISTANCE: 500MΩMIN. AT 500V DC.
5. DIELECTRIC STRENGTH: 1000 VAC 50Hz 1MINUTE

MECHANICAL:

1. SHIELD: BRASS T=0.2MM, Finish: 30u" Nickel
2. HOUSING /INSERT MATERIAL:
THERMOPLASTIC, PBT UL94V-0.COLOR BLACK
3. CONTACT MATERIAL: PHOSPHOR BRONZE T=0.35MM
4. PLATING: GOLD PLATING OVER NICKEL, PLATED NICKEL 30-50U". SN 100-120U. GOLD PLATED ON CONTACT AREA FU/3U/6U/15U/30U/50U"
5. OPERATING LIFE: 750 CYCLES MIN.

ENVIRONMENTAL:

1. STORAGE: -40° C TO +85° C
2. OPERATION: 0° C TO 75° C

LED ELECTRICAL CHARACTERISTIC				
		Green	Green	
		9	11	12
		LEFT LED	RIGHT LED	

Standard LED	Wavelength	Forward V (Min/Max)	Forward A	Type
Green	568nm	1.8V/2.8V	20mA	squareness
Yellow	585nm	1.8V/2.8V	20mA	squareness
Orange	610nm	1.8V/2.8V	20mA	squareness

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.30

UNIT / mm

SCALE 1 : 1

.XX ± 0.20

DATE

.XXX ± 0.10

ANG ±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

MJF13UL-KT06B3GG-0808-LF

SERIES | | | | LEADFREE
BLACK | | | | 8P8C
06u" GOLD | | | | GREEN / GREEN
TOP SPRING | | | | REAR TAB 3.43mm

DESCRIPTION: Shielded RJ45 Modular Jack, Through Hole Type, with LED, Ports

煜倫股份有限公司

www.morethanall.com