



**Electrical:**  
 1.Voltage Rating:125 Vac Rms.  
 2.Current Rating:1.5 Amp.  
 3.Contact Resistance:40 Milliohms Max.  
 4.Insulation Resistance:1000 Megohms Min @500 Vdc.  
 5.Dielectric Strength:1000 Vac Rms 60Hz, 1Min.

**Mechanical:**  
 1.Operating:750 Cycles Min.

**Environmental:**  
 1.Storage:-40°C To +85°C.  
 2.Operation:-20°C To +75°C.

Mates With Modular Plug Conforming To FCC Part 68, Subpart F.

**MATERIALS:**  
 PLASTIC HOUSING: ENGINEERING THERMOPLASTIC  
 FLAMMABILITY RATING UL 94V-0.

CONTACTS: PHOSPHOR BRONZE  
 PLATING: GOLD PLATING OVER NICKEL IN CONTACT,  
 TIN PLATING OVER NICKEL IN SOLDER AREA.  
 SHIELD: BRASS PLATING NICKEL ALLOY.

P.C.B LAYOUT/TOP VIEW

(warranty : 12 month within 50% of humidity)

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
 .X ± 0.38  
 .XX ± 0.25  
 .XXX ± 0.10  
 ANG ± 3°

P PROJECTION



**ORDER INFORMATION**

MJF13UL-YF06B3YG-0808

SERIES 8P8C  
 YELLOW LED2 / LED1  
 FULL SPRING YELLOW / GREEN  
 REAR TAB 3.43mm  
 06u" GOLD

DESCRIPTION: