



PCB LAYOUT (Ref.)

MATERIAL:

- HOUSING—DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL94V-0
 - CONTACTS—0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.
 - SHIELD—0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION

照片框

ORDER INFORMATION

MJF13ULA4-KF06B3xx-0808-LF

SERIES
LEAD FREE
8P8C
GY:GREEN/YELLOW
YG:YELLOW / GREEN
BLACK FULL SPRING
REAR TAB 3.43mm
06u" GOLD

DESCRIPTION: 4PORTS, RJ45, WITH LED S SHIELDED, SIDE ENTRY PCB GANGED JACK