



PCB LAYOUT (Ref.)

MATERIAL:

- HOUSING—DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL94V-0
- CONTACTS—0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.
- SHIELD—0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.

CAVITY CONFIRMS TO FCC RULES AND REGULATIONS
PART 68,SUBPART F.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.±

.X±

.XX±

.XXX±

ANG ±

PJECTION

照片框

ORDER INFORMATION

MJF13ULA4-KF06B3GY-0808-LF

SERIES LEAD FREE
8P8C
GREEN/YELLOW
REAR TAB 3.43mm
BLACK 06u" GOLD
FULL SPRING

DESCRIPTION: 4PORTS, RJ45, WITH LED'S SHIELDED, SIDE ENTRY PCB GANGED JACK