



PCB LAYOUT (Ref.)

MATERIAL:

- HOUSING—DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL94V-0
 - CONTACTS—0.35mm THICK PHOS-BRONZE PLATED
WITH HARD GOLD AND GOLD FLASH IN
SOLDER AREA.
 - SHIELD—0.25mm THICK COPPER ALLOY,
PLATED WITH NICKEL.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X.±

CHECKED BY GENIUS

.X±

UNIT / mm

SCALE 1:1

.XX±

DATE

.XXX±

ANG ±

煜倫股份有限公司

www.morethanall.com

SIZE A4

PJECTION

照片框

ORDER INFORMATION

MJF13JLA4-KF06B3GYGY-0808-LF

SERIES

LEAD FREE

8P8C

LED1:GREEN/YELLOW LED2:GREEN/YELLOW

BLACK REAR TAB 3.43mm

06u" GOLD FULL SPRING

DESCRIPTION:4PORTS, RJ45, WITH LED'S SHIELDED, SIDE ENTRY PCB GANGED JACK