



**PCB LAYOUT**  
(Top View)

**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Delectric Voltage : 1,000 Vrms 60 Sec. Min.

**2. Physical char.**

- Housing : Nylon (UL 94V-0)
- Color : Black Color
- Spring Wire : 0.35mm Thickness Phosphor Bronze  
Gold Plating Over Nickel
- Temperature Range : - 25 /+90 Deg C
- Durability : 500 Mating cycles Min.

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

**ORDER INFORMATION**

MJF13ULA4-KF06B3RY-0808-LF

SERIES | | | | LEAD FREE  
BLACK | | | | 8P8C  
| | | | RED/YELLOW  
| | | | REAR TAB 3.43mm  
| | | | 06u" GOLD  
| | | | FULL SPRING

DESCRIPTION: