



**PCB LAYOUT**  
(Top View)

**SPECIFICATION :**

**1. Electrical Char.**

- Insulation Resistance : 500M-Ohm Min.**
- Contact Resistance : 20milli-Ohm Max.**
- Rating Current : 1.5A Max.**
- Rating Voltage : 120V AC.**
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.**

**2. Physical char.**

- Housing : Nylon (UL 94V-0)**
- Color : Black Color**
- Spring Wire : 0.35mm Thickness Phosphor Bronze**
- Gold Plating Over Nickel**
- Temperature Range : - 25 /+90 Deg C**
- Durability : 500 Mating cycles Min.**

MJF13ULA8-KF06B3xxxx-0808

RYGX:RED+YELLOW/GREEN  
RYGR:RED+YELLOW/GREEN+RED

RoHS Compliant



PART NO. MJF13ULA8-KF06B3xxxx0808

DWG NO. MJF13ULA8-KF06B3xxxx0808

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

.X ± 0.2  
.XX ± 0.1  
.XXX ±  
AWG

DESCRIP TION:			
AREA	REVISIONS	HK	DATE

煜倫股份有限公司