

## PCB LAYOUT(Top View)

### MATERIAL AND FINISH

HOUSING : LCP POLYESTER UL-94V-0 MIXED GLASS FIBER.  
STANDARD COLOR FIBER.  
CONTACT : 0.35mm THICK PHOSPHOR BRONZE PLATED WITH NICKEL.  
CONTACT PLATED : GOLD 15u".  
SHIELD : 0.20mm THICK COPPER ALLOY PLATED WITH NICKEL.

### ELECTRICAL:

1. CURRENT RATING : 1.5 AMP.
2. VOLTAGE RATING : 150 VAC.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MILLIOHMS MIN.
5. DIELECTRIC WITHSTANDING VOLTAGE : 1000 VAC, 1MIN.

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES  
煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ±  
.XX ±  
.XXX ±  
ANG ±



### ORDER INFORMATION

MJF16U-KX15B36-0808-LF

SERIES | 8P8C LEADFREE  
REAR TAB 3.68mm  
15u" GOLD  
NON EAR  
BLACK

DESCRIPTION:

www.morethanall.com