



RECOMMENDED PCB LAYOUT
TOP VIEW

SPECIFICATION

MECHANICAL:

HOUSING MATERIAL: HIGH TEMP THERMOPLASTIC
UL94V-0, BLACK

CONTACT MATERIAL: PHOSPHOR BRONZE T=0.35mm,
PLATED WITH GOLD FLASH 3 μ IN CONTACT AREA
AND TIN IN SOLDER AREA

SHIELD MATERIAL: BRASS, NICKEL PLATING

ELECTRICAL:

CURRENT RATING: 1.5 A

CONTACT RESISTANCE: 50m MAX.

INSULATION RESISTANCE: 500m MIN.

DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC, 1 MINUTE.

LED COLOR: GREEN, GREEN

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, \pm
.X \pm 0.20
.XX \pm 0.15
.XXX \pm 0.10
ANG \pm 1°

PJECTION

照片框

ORDER INFORMATION

MJF25ULB1-KF06B7GG-0808-LF

SERIES

LEADFREE

8P8C

LED1/GREEN LED2/GREEN

REAR TAB 7.11mm

BLACK 6u" GOLD
FULL SPRING

DESCRIPTION: