

**NOTES:**

**ELECTRICAL:**

1. VOLTAGE RATING:125VAC RMS.
2. CURRENT RATING:1.5AMP.
3. CONTACT RESISTANCE:42MILLIOHMS MAX.
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH:1000 VDC RMS 60HZ. 1MIN.

**MECHANICAL:**

1. HOUSING MATERIAL:NYLON 66, UL94V-0.
2. CONTACT MATERIAL:PHOSPHOR BRONZE φ0.46mm.
3. PLATING:GOLD PLATING OVER NICKEL.
4. OPERATING LIFE:250 CYCLES MIN.
5. PCB RETENTION PRE-SOLDER:1 LB MIN.
6. PCB RETENTION POST-SOLDER:10 LBS MIN.

**ENVIRONMENTAL:**

1. STORAGE:-40°C TO 85°C.
2. OPERATION:0°C TO 70°C.

RoHS Compliant



PART NO. MJF27ULB4-KF03A4GG-0808

DWG NO. MJF27ULB4-KF03A4GG-0808

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.25  
.XX ± 0.15  
.XXX ± 0.10  
AWG

DESCRIPTION:

TELEPHONE JACK 2\*4PORT  
腳前4.57mm 有彈片 帶LED燈

AREA

REVISIONS

HK

DATE

煜倫股份有限公司