



PC Board Layout

NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS.
2. CURRENT RATING: 1.5 AMP.
3. CONTACT RESISTANCE: 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 500 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH: 1000 VAC RMS 50Hz or 60Hz, 1MIN.

MECHANICAL:

1. HOUSING & INSERT MATERIAL: PA46 UL94V-0.
2. INSERT: PBT UL94V-0.
3. CONTACT MATERIAL: DIAMETER 0.45MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL.
4. SHIELD: 0.20 ~ 0.25MM THICKNESS BRASS WITH NICKEL PLATED.
5. MATING/UNMATING FORCE: 2.2KG.F MAX.
6. RETENTION STRENGTH: 7.7KG.F MIN BETWEEN JACK AND PLUG.
7. OPERATING LIFE: 750 CYCLES MIN.

ENVIRONMENTAL:

1. STORAGE: -40°C ~ +85°C RELATIVE HUMIDITY<70%.
2. OPERATION: -40°C ~ +85°C.

Remark:

The mark with ★ is the key inspection dimension for QC

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±

CHECKED BY GENIUS

.X ± 0.25

UNIT / mm

SCALE 1 : 1

.XX ± 0.15

.XXX ± 0.05

DATE

ANG ±

SIZE A4

P PROJECTION

照片框

ORDER INFORMATION

MJF27ULB8-KF06A4cc-0808

SERIES

8P8C

LED1 / LED2

GY:GREEN / YELLOW

YG:YELLOW / GREEN

BLACK

FRONT TAB 4.7mm

FULL SPRING 06u" GOLD

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: