



NOTES:

ELECTRICAL:

- 1. VOLTAGE RATING : 125 VAC.
- 2. CURRENT RATING : 1.5 AMP.
- 3. CONTACT RESISTANCE : 50 MILLIOHMS MAX.
- 4. INSULATION RESISTANCE: 1000 MEGOHMS MIN. @ 500 VDC.
- 5. DIELECTRIC STRENGTH : 1000 VAC 60Hz, 1MIN.

MECHANICAL:

- 1. HOUSING MATERIAL : GLASS FILLED POLYESTER OR HIGH TEMP. UL94V-0.
- 2. CONTACT MATERIAL : PHOSPHOR BRONZE t=0.35mm
- 3. PLATING : 1: CONTACT AREA- SELECTIVE GOLD PLATING.
2: TAILS-PLATED TIN OVER NICKEL.
GOLD PLATING OVER NICKEL.
- 4. OPERATING LIFE : 750 CYCLES MIN.
- 5. PCB RETENTION PRE-SOLDER : 1 LB MIN.
- 6. PCB RETENTION POST-SOLDER: 10 LBS MIN.
- 7. LED SIZE : 3.2*2.0*4.0*P=2.29mm

ENVIRONMENTAL:

- 1. STORAGE : -40°C TO +85°C.
 - 2. OPERATION: -40°C TO +85°C.
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.

MJF27ULBx-KF06A4xx-0808

GR:GREEN/RED

- 2:2X02PORTS
- 3:2X03PORTS
- 4:2X04PORTS
- 6:2X06PORTS
- 8:2X08PORTS

RoHS Compliant

PORTS	N	A±0.25	B±0.25	C±0.05
2x8	7	113.82	130.95	113.82
2x6	5	81.30	98.43	81.30
2x4	3	48.78	65.91	48.78
2x3	2	32.52	49.45	32.52
2x2	1	16.26	33.39	16.26

MORETHANALL
CONNECTORS
ASSEMBLIES

PART NO. MJF27ULBx-KF06A4xx-0808

DWG NO. MJF27ULBx-KF06A4xx-0808

FILE NO.

UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION

TOLERANCES ARE

- .X ± 0.2
- .XX ±
- .XXX ±
- AWG

DESCRIPTION: 2XN STACKED LED JACK

AREA REVISIONS HK DATE

焯倫股份有限公司