



Electrical

- 1.Current Rating:1.5Amp Max
- 2.Voltage Rating:150Volts
- 3.Contact Resistance:20m-ohm
- 4.Insulation Resistance:500M-ohm
- 5.Dielectric Withstand Voltage:1000VAC RMS, 60HZ 1MIN.

Materials

- 1.Housing:ABS UL94V-0
- 2.IDC:PC UL94V-0, Accept 22-26 AWG Solid Wire
- 3.PCB:FR4 1.6mm thickness 2 layers
- 4.Contact:PC UL94V-0,0.45mm Diameter phosphor bronze with Gold plating on contact area.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X, ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MJK16C5E-CKP50-0808-LF

SERIES

50u"

8P8C

LEADFREE

PLASTIC

BLACK

IDC

DESCRIPTION: Cat.5e Keystone Jack Unsh e d Hor zonta Type