


MATERIALS:

- HOUSING-DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL 94V-0
OR-NYLON ZYTEL FR-52
HEAT DEFLECTION TEMP.278°
BLACK COLOR, UL 94V-0
 - TERMINAL-0.35mm THICK PHOS-BRONZE
PLATED WITH HARD GOLD AND
TIN/LEAD IN SOLDER AREA.
 - HOLD DOWN-0.35mm THICK COPPER ALLOY,
PLATED WITH TIN-LEAD.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS

NOTE:

1. A AND B HIGHEST POINT MUST OVER C FLAT SURFACE.
2. THE MAXIMUM DISTANCE (0.15m/m) BETWEEN LOWEST AND HIGHEST ON A AND B FLAT SURFACE.



PCB LAYOUT

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30

.X ± 0.25

.XX ± 0.13

.XXX ± 0.05

ANG ±

PJECTION

照片框

ORDER INFORMATION

MJV13-KXxx-0808-LF

SERIES

LEADFREE

8P8C

06:06u" GOLD

15:15u" GOLD

BLACK

NON EAR

DESCRIPTION: 8 POSITION TOP ENTRY SMT TYPE W/O BOARD LOCK PCB JAVK