



PCB LAYOUT

MATERIALS:

- HOUSING-DSM STANYL TE250F6 (NYLON-46)
HEAT DEFLECTION TEMP.290°
BLACK COLOR, UL 94V-0
 - OR-NYLON ZYTEL FR-52
HEAT DEFLECTION TEMP.278°
BLACK COLOR, UL 94V-0
 - TERMINAL-0.35mm THICK PHOS-BRONZE
PLATED WITH HARD GOLD AND
TIN/LEAD IN SOLDER AREA.
 - HOLD DOWN-0.35mm THICK COPPER ALLOY,
PLATED WITH TIN-LEAD.
- CAVITY CONFIRMS TO FCC RULES AND REGULATIONS

NOTE:

- A AND B HIGHEST POINT
MUST OVER C FLAT SURFACE.
- THE MAXIMUM DISTANCE (0.15m/m)
BETWEEN LOWEST AND HIGHEST
ON A AND B FLAT SURFACE.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.25
.XX ± 0.13
.XXX ± 0.05
ANG ±

PJECTION

照片框

ORDER INFORMATION

MJV13-KXxxP-0808-LF

SERIES LEADFREE

8P8C

POST

BLACK 06:06u" GOLD
NON EAR 15:15u" GOLD

DESCRIPTION: 8 POSITION TOP ENTRY SMT TYPE BOARD LOCK 3.00 PCB JACK