



PCB LAYOUT
COMPONENT SIDE SHOWN

NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 35 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE t=0.35mm.
3. PLATING : 1. CONTACT AREA- SELECTIVE GOLD PLATING.
2. TAILS- 150μ" TIN-LEAD MIN OVER 50μ" NICKEL.
4. OPERATING LIFE : 750 CYCLES MIN.

- △ 5. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

1. STORAGE: -40°C TO +85°C.
2. OPERATION: 0°C TO 70°C.

MATES WITH MODULAR PLUG CONFORMING TO
FCC PART 68, SUBPART F.



PART NO. MJV15-KFExxP2-0808

DWG NO. MJV15-KFExxP2-0808

FILE NO.

UNIT / mm

SCALE 1:1

APPROVED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

.X ± 0.2
.XX ± 0.15
.XXX ± 0.075
AWG

DESCRIPTION:

TOP ENTRY PCB JACK 8P (SMT)

AREA

REVISIONS

HK

DATE

煜倫有限公司