



PCB LAYOUT/TOP VIEW

Electrical:

- 1.Voltage Rating:125 Vac Rms.
- 2.Current Rating:1.5 Amp.
- 3.Contact Resistance:40 Milliohms Max.
- 4.Insulation Resistance:1000 Megohms Min @500 Vdc.
- 5.Dielectric Strength:1000 Vac Rms 60Hz, 1Min.

Mechanical:

- 1.Operating:750 Cycles Min.

Environmental:

- 1.Storage:-40°C To +85°C.
 - 2.Operation:-20°C To +75°C.
 - 3.IR Reflow Soldering Temperature:255°C To 265°C(5~10 Seconds).
- Mates With Modular Plug Conforming To FCC Part 68, Subpart F.

MATERIALS:

PLASTIC HOUSING: HIGH TEMP THERMOPLASTIC
FLAMMABILITY RATING UL 94V-0.

CONTACTS: PHOSPHOR BRONZE

PLATING: GOLD PLATING OVER NICKEL IN CONTACT.

TIN PLATING OVER NICKEL IN SOLDER AREA.

SOLDER PAD: BRASS WITH TIN PLATING OVER NICKEL.

SHIELDED: BRASS WITH NICKEL PLATED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm

SCALE 1:1

DATE

SIZE A4

X, ± 0.50

.X, ± 0.38

.XX, ± 0.25

.XXX, ± 0.10

ANG ± 3°

PJECTION

照片框

ORDER INFORMATION

MJVF12-KXxx-0808-LF

SERIES

8P8C

LEADFREE

- 06:06u" GOLD
- 15:15u" GOLD
- 30:30u" GOLD
- 50:50u" GOLD

NON EAR

DESCRIPTION: