



- Material
- 2.1 Housing : 9T Polyester UL94V-0, Color- See Part NO.
 - 2.2 Terminal : 0.30 ± 0.10 mm Thickness Phosphor Bronze
 - 2.3 Hold Down : 0.40 ± 0.10 mm Thickness Brass.

- Finish
- 3.1 Contact: AU On Contact Area 3μ "
Solder Area Sn 80μ " Min, Nickel Plating 50μ " Min.
 - 3.2 Hold Down : 50μ " Min Nickel Plated Overall.

- Specification:
- 4.1 Mating: AC 125V 1.5A.
 - 4.2 Contact resistance $\leq 60m\Omega$.
After test: $\leq 60m\Omega$.
 - 4.3 Insulation resistance: (DC 500V)
 $500M\Omega$.
After test: $\geq 200M\Omega$.
 - 4.4 Withstanding voltage: 500V AC.
 - 4.5 Mating force: 25N Max.
 - 4.6 Life test: 1000 cycles Min.
 - 4.7 Lead Soldering Temperature
Housing Material 9T = $260 \pm 5^\circ$ 10s

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, \pm
.X ± 0.50
.XX ± 0.30
.XXX ± 0.15
ANG \pm

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

照片框

ORDER INFORMATION

MJW13U-KX03EP2-0808-LF

SERIES

LEADFREE
8P8C
EAR+POST
03u" GOLD
NON EAR
BLACK

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: RJ45 Connector Side Entry Modular Jack-SMT