



PCB LAYOUT

MATERIAL AND FINISH

HOUSING : LCP POLYESTER UL-94V-0 MIXED GLASS FIBER.
 STANDARD COLOR FIBER.
 CONTACT : 0.30mm THICK PHOSPHOR BRONZE PLATED WITH NICKEL.
 CONTACT PLATED : GOLD 3u".
 SHIELD : 0.20mm THICK COPPER ALLOY PLATED WITH NICKEL.

ELECTRICAL:

1. CURRENT RATING : 1.5 AMP.
2. VOLTAGE RATING : 150 VAC.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MILLIOHMS MIN.
5. DIELECTRIC WITHSTANDING VOLTAGE : 1000 VAC, 1MIN.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES
 煜倫股份有限公司

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.50
 .XX ± 0.25
 .XXX ± 0.05
 ANG ± 1°

PPOJECTION

照片框

ORDER INFORMATION

MJWF06U-KX03MP-0808-LF

SERIES | | | | LEADFREE
 8P8C
 METAL POST
 03u" GOLD
 NON EAR
 BLACK

DESCRIPTION:

www.morethanall.com