



PCB LAYOUT
(Top View)

SPECIFICATION :

1. Electrical Char.

- Insulation Resistance : 500M-Ohm Min.
- Contact Resistance : 20milli-Ohm Max.
- Rating Current : 1.5A Max.
- Rating Voltage : 120V AC.
- Dielectric Voltage : 1,000 Vrms 60 Sec. Min.

2. Physical char.

- Housing :
Nylon (UL 94V-0), Soldering Temperature:260°C
- Color : Black Color
- Spring Wire :
0.35mm Thickness Phosphor bronze Gold Plating Over Nickel
- Shielded : Brass Plating Nickel
- Temperature Range : - 40°C / +85°C
- Durability : 500 Mating cycles Min.

RoHS Compliant

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

- X, ±
- .X ± 0.20
- .XX ± 0.10
- .XXX ±
- ANG ±

P PROJECTION

照片框

ORDER INFORMATION

MJWF13UL-KF06B3YG-0808

SERIES

BLACK

06u" GOLD

REAR TAB 3.43mm

FULL SPRING

8P8C

YELLOW / GREEN

DESCRIPTION: RJ45 SIDE ENTRY S.M.T. JACK WITH LED