



A5 RECOMMENDED P.C.B LAYOUT

Specification

- 1.Current Rating:3A AC/DC
- 2.Voltage Rating:250V AC/DC
- 3.Contact Resistance:20mΩ Max.
- 4.Insulation Resistance:1000MΩ Min.
- 5.Withstand Voltage:AC1000V/Minute
- 6.Operating Temperature:-25°C~+85°C

Material:

- 1.Housing:Thermoplastic UL94V-0
- 2.Contact Pin:Copper Alloy SQ. Pin 0.64mm

PIN	DIM.A	DIM.B	PIN	DIM.A	DIM.B	PIN	DIM.A	DIM.B	PIN	DIM.A	DIM.B
02	2.54	5.10	08	17.78	20.44	13	30.48	33.20	18	43.18	45.94
04	7.62	10.24	09	20.32	23.00	14	33.02	35.74	19	45.72	48.50
05	10.16	12.78	10	22.86	25.54	15	35.56	38.30	20	48.26	51.05
06	12.70	15.24	11	25.40	28.10	16	38.10	40.84			
07	15.24	17.88	12	27.94	30.64	17	40.64	43.40			

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±  
X ± 0.35  
.XX ± 0.25  
.XXX ± 0.15  
ANG ±

照片框

ORDER INFORMATION

MKL-D-xx-LF  
SERIES | LEADFREE  
02-20WAY  
DIP 180°

DESCRIPTION: