



Notes:

1. Current Rating : 3A ^(B)
2. Current Voltage : 250V AC,DC
3. Contact Resistance : 20mΩ Max.
4. Insulation resistance:1000M Ω Min
5. Withstanding Voltage : 1000V AC for 1 Minute.
6. Operating Temperature : -25°C~85°C

Pin No.	Dim. A	Dim. B	Pin No.	Dim. A	Dim. B
2	2.54	5.08	10	22.86	25.40
3	5.08	7.62	11	25.40	27.94
4	7.62	10.16	12	27.94	30.48
5	10.16	12.70	13	30.48	33.02
6	12.70	15.24	14	33.02	35.56
7	15.24	17.78	15	35.56	38.10
8	17.78	20.32	16	38.10	40.64
9	20.32	22.86			

2	Contact	Brass, Tin Plated	xx
1	Insulator	Nylon 66 UL 94V-0, White	1
No.	Part Name	Specifications	Qt'y

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MKL-DD37WH-xx-LF
SERIES | | | LEADFREE
| | | 02~16WAY
| | | WHITE
| | | DIP 3.7mm
| | | DIP 180°

DESCRIPTION: