



SPECIFICATIONS

Current Rating: 4A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Tin-plated
 Material: Nylon 66,UL94V-2
 Pantone Color: 1685C

Ordering Information & Dimensions

| PART NO. | Dimensions | |
|-----------|------------|-------|
| | A | B |
| MKL-RV-02 | 2.54 | 5.08 |
| MKL-RV-03 | 5.08 | 7.62 |
| MKL-RV-04 | 7.62 | 10.16 |
| MKL-RV-05 | 10.16 | 12.70 |
| MKL-RV-06 | 12.70 | 15.24 |
| MKL-RV-07 | 15.24 | 17.78 |
| MKL-RV-08 | 17.78 | 20.32 |
| MKL-RV-09 | 20.32 | 22.86 |
| MKL-RV-10 | 22.86 | 25.40 |
| MKL-RV-11 | 25.40 | 27.94 |
| MKL-RV-12 | 27.94 | 30.48 |
| MKL-RV-13 | 30.48 | 33.02 |
| MKL-RV-14 | 33.02 | 35.56 |
| MKL-RV-15 | 35.56 | 38.10 |
| MKL-RV-16 | 38.10 | 40.64 |
| MKL-RV-17 | 40.64 | 43.18 |
| MKL-RV-18 | 43.18 | 45.72 |
| MKL-RV-19 | 45.72 | 48.26 |
| MKL-RV-20 | 48.26 | 50.80 |

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X.±
 .X±
 .XX±
 .XXX±
 ANG±

照片框

ORDER INFORMATION

MKL-RV-xx-LF
 SERIES | LEADFREE
 | 02~20WAY
 | REVERSED
 | DIP 90°

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com