



RECOMMENDED P. C. B LAYOUT

**SPECIFICATIONS**

- Current Rating:  
3 Amp
- Voltage Rating:  
250V
- Contact Resistance:  
20 m ohms Max.
- Insulator resistance:  
5000 Megohms Min.
- Dielectric withstanding:  
AC 500V/minute
- Operating Temperature:  
-40° ~ +105°C
- Contact Material:  
Brass
- Insulator Material:  
Nylon-6T UL94V-0
- Color:Natural
- Finish:  
Gold, Tin or Duplex plated  
Duplex plated:  
Gold plated on contact area  
Tin on solder area

**RoHS Compliant**

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.50  
.XX ± 0.25  
.XXX ±  
ANG ± 3°

P PROJECTION

照片框

**ORDER INFORMATION**

MKL-RWH11S-08-LF  
SERIES | | | | LEADFREE  
| | | | 08 WAY  
| | | | BASE  
| | | | 11.5mm  
| | | | WHITE  
| | | | DIP 90°

DESCRIPTION: