



Conteract:

Contact:Brass.

Insuiator:Nylon 9T.

Finish:Gold flash plated over nickel.

Circuits	Dimension		
	A	B	C
10	10.0	25.9	8.0
12	12.0	27.9	10.0
14	14.0	29.9	12.0
16	16.0	31.9	14.0
20	20.0	35.9	18.0
22	22.0	37.9	22.0
24	24.0	39.9	22.0
26	26.0	41.9	24.0
30	30.0	45.9	28.0
32	32.0	47.9	30.0
34	34.0	49.9	32.0
40	40.0	55.9	38.0
44	44.0	59.9	42.0
50	50.0	65.9	48.0
60	60.0	75.9	58.0

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ± 0.30
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ± 1°

P PROJECTION

照片框

ORDER INFORMATION

ML-RGxx-xxx-LF
SERIES | LEADFREE
010-060 WAY
G15:FULL GOLD 15u"
DIP 90°

DESCRIPTION: