


PCB MOUNT HOLES

NOTE:

- 1.Impedance:50Ω
- 2.Frequency Range:DC 0-6 GHz
- 3.Voltage Rating:250 Vrms
- 4.Contact Resistance:Center Contacts:10 mΩ Max
Outer Contacts:5 mΩ Max
- 5.Insulation Resistance:5000 MΩ MIN.
- 6.Interface in Accordance With:BS EN 122340
- 7.Operating Temperature Range:-65°~165°C



3	CONTACT PIN	Be,Cu	1	GOLD PLATED
2	INSULATOR	TEFLON	1	WHITE
1	BODY	BRASS	1	GOLD PLATED
ITEM	DESCRIPTION	MATERIAL	Q'TY	FINISHED

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

0.5-15 = ±0.15
15-30 = ±0.30
30-120 = ±0.60
>120 = ±1.00
ANGLES
±5°

PJECTION

照片框

ORDER INFORMATION

MMCX-JVM23-50-LF

SERIES | | | LEADFREE
50 OHM
METAL FOOT 2.36mm
180°SMT
JACK

DESCRIPTION: MMCX STRAIGHT RECEPTACLE JACK