



ELECTRICAL SPECIFICATIONS:
 Impedance: 50 OHM
 FREQUENCY Range: 0-6 GHz
 VSWR: 1.6max

ENVIRONMENTAL:
 Temperature: -55°C~155°C

| | | | | |
|----|-------------|----------|--------|------|
| 3 | PIN | BE CU | GOLD | 1 |
| 2 | INSULATOR | PTFE | NONE | 1 |
| 1 | BODY | BRASS | GOLD | 1 |
| NO | DESCRIPTION | MATERIAL | FINISH | Q'TY |

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

ANGLES = ±3
 UP TO 6 = ±0.1
 6-40 = ±0.2
 40-120 = ±0.6
 120-315 = ±1.0
 ABOVE 315 = ±1.6

照片框

ORDER INFORMATION

MMCX-JW-50-LF

SERIES | | LEADFREE
 | | 50 OHM
 | 90°SMT
 JACK

DESCRIPTION: MMCX(F)7.5L 50 OHM TGG