



注意方向性 SMA剖面與MMCX向下

BILL OF MATERIAL			
ITEM	Q'TY	PART NO.	DESCRIPTION
1	1	SAC0273TGGK	SMA FEMALE BKD CRIMP
2	1	MMB0201TGGL	MMCX MALE R/A CRIMP
3	1	HSE178	HANNSTAR #32*1C $\phi$ 1.13mm (white)
4	2	HT000007	HEAT SHRINK TUBING $\phi$ 3.0*15mm (WHITE)
5	1		Washer <華司>
6	1		Nut <螺帽>

PS: 3 MHz FREQUENCY RANGE  
 50 OHM  
 INSERTION LOSS  $\leq$  0.2 dB  
 RETURN LOSS  $\leq$  -15 dB  
 V.S.W.R.  $\leq$  1.3

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X,  $\pm$   
 .X  $\pm$   
 .XX  $\pm$   
 .XXX  $\pm$   
 ANG  $\pm$

PJECTION

照片框

ORDER INFORMATION

MMCXSMA-1R1S113-E7C-LF

SERIES

LEADFREE

70mm

MALE TO FEMALE

RG113

RT/ST

DESCRIPTION: SMA FEMALE BKD- $\phi$ 1.13-MMCX MALE R/A