


Recommended P.C.B Layout(Top Side)  
(PCB BOARD TOLERANCE±0.05)

### SPECIFICATIONS

Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC   
 Temperature Range: -55°C to +125°C  
 Contact Resistance: 20mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1000V AC/minute  
 Pin Material: Brass/Tin-plated  
 Material:LCP,UL94V-0

Part No.	Dimension	
	A	B
MNM-PRX-2X02	2.54	6.60
MNM-PRX-2X03	5.08	9.14
MNM-PRX-2X04	7.62	11.68
MNM-PRX-2X05	10.16	14.22
MNM-PRX-2X06	12.70	16.76
MNM-PRX-2X07	15.24	19.30
MNM-PRX-2X08	17.78	21.84
MNM-PRX-2X09	20.32	24.38
MNM-PRX-2X10	22.86	26.92
MNM-PRX-2X11	25.40	29.46
MNM-PRX-2X12	27.94	32.00
MNM-PRX-2X13	30.48	34.54
MNM-PRX-2X14	33.02	37.08
MNM-PRX-2X15	35.56	39.62
MNM-PRX-2X16	38.10	42.16
MNM-PRX-2X17	40.64	44.70
MNM-PRX-2X18	43.18	47.24
MNM-PRX-2X19	45.72	49.78
MNM-PRX-2X20	48.26	52.32
MNM-PRX-2X21	50.80	54.86
MNM-PRX-2X22	53.34	57.40
MNM-PRX-2X23	55.88	59.94
MNM-PRX-2X24	58.42	62.48
MNM-PRX-2X25	60.96	65.02

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±  
 X ± 0.40  
 .XX ± 0.25  
 .XXX ±  
 ANG ±

PPOJECTION 

照片框

ORDER INFORMATION

MNM-PRX-2Xxx-LF  
 SERIES | LEADFREE  
 2X02:04WAY  
 2X25:50WAY  
 NON POST  
 DIP 90°  
 MALE

DESCRIPTION: 2.54mm WAFER 90° DIP