



SPECIFICATIONS

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Pin Material: Brass/Tin-plated
 Material: PBT,UL94V-0
 Color: (Black)

Ordering Information & Dimensions

PART NO.	Dimensions		
	A	B	C
MOD-D-1X02	2.54	7.62	6.22
MOD-D-1X03	5.08	10.16	8.76
MOD-D-1X04	7.62	12.70	11.30
MOD-D-1X05	10.16	15.24	13.84
MOD-D-1X06	12.70	17.78	16.38
MOD-D-1X08	17.78	22.86	21.46
MOD-D-1X10	22.86	27.94	26.54

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±
 X, ±
 .XX ±
 .XXX ±
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

MOD-D-1Xxx-LF
 SERIES | LEADFREE
 1X02:02WAY
 1X10:10WAY
 DIP 180°

DESCRIPTION: 2.54 180° Single Row Wafer